



KFS 03 - RF



- Footswitch Polyamid, glasfilled
- 2,4 GHz technology, Bluetooth LE 4.0
- Various receiver options available

Base Option

- 1. Black RAL 9017
- 2. Grey RAL 7035
- A. Customized

Cover Option

- 1. Cover black RAL 9017
- 2. Cover graphite grey RAL 7024
- 3. Cover lightgrey RAL 7035
- 4. Cover blue RAL 5017
- 5. Cover green RAL 6024
- 6. Cover yellow RAL 1023
- 7. Cover red RAL 3020
- A. Customized

Norms

- A. Customized
- Z. No Norm

KFS03.RF.

Switching Action / Receiver Options

- 1. S.P.S.T. - N/O, 0,1 A / 24 VDC, Receiver PCB with semiconductor relays up to 0,2 A; for system integration.
- 2. S.P.S.T. - N/O, 0,1 A / 24 VDC, Receiver with housing; semiconductor relays up to 0,2 A, cordset.
- 3. S.P.S.T. - N/O, 0,1 A / 24 VDC; Receiver with USB interface
- A. Customized

Protection

- 1. IP X2
- A. Customized

Receiver Cordset

- 1. 2 m
- 2. 5 m
- 3. 10 m
- A. Customized
- Z. No Cordset

Accessories

Part-No.

- 1. Panel large 4.69C.0005
- 2. Guard 4.69C.0001
- 3. Loading plate with anti slip pad 4.69C.0015
- A. Customized
- Z. No accessories

- Secure wireless contact up to 10m line of sight
- application-specific range depends on the installation location