



KFS 03 - RF



- Footswitch Polyamid, glasfilled
- 2,4 GHz technology, Bluetooth LE 4.0
- Various receiver options available

Base Option

- 1. Black RAL 9017
- 2. Grey RAL 7035
- A. Customized

Cover Option

- 1. Cover black RAL 9017
- 2. Cover graphite grey RAL 7024
- 3. Cover lightgrey RAL 7035
- 4. Cover blue RAL 5017
- 5. Cover green RAL 6024
- 6. Cover yellow RAL 1023
- 7. Cover red RAL 3020
- A. Customized

Norms

- A. Customized
- Z. No Norm

KFS03.RF.

Switching Action / Receiver Options

- 1. S.P.S.T. - N/O, 0,1 A / 24 VDC, Receiver PCB with semiconductor relays up to 0,2 A; for system integration.
- 2. S.P.S.T. - N/O, 0,1 A / 24 VDC, Receiver with housing; semiconductor relays up to 0,2 A, cordset.
- 3. S.P.S.T. - N/O, 0,1 A / 24 VDC; Receiver with USB interface
- A. Customized

Protection

- 1. IP X2
- A. Customized

Receiver Cordset

- 1. 2 m
- 2. 5 m
- 3. 10 m
- A. Customized
- Z. No Cordset

Accessories

Part-No.

- 1. Panel large 4.69C.0005
- 2. Guard 4.69C.0001
- 3. Loading plate with anti slip pad 4.69C.0015
- A. Customized
- Z. No accessories

- Secure wireless contact up to 10m line of sight
- application-specific range depends on the installation location



KMP 02-RF

- Wireless 2-pedal footswitch
- Robust and reliable
- Long Batterie life time



Norms

- A. Customized
- Z. No Norm

Panel-Colour

1. Black RAL 9017
 2. Graphitegrey RAL 7024
 3. Lightgrey RAL 7035
- A. Customized

Base plate

1. ABS (Standard)
 2. Stainless Steel
- A. Customized

Accessories

Part-No.

- | | |
|-------------------|------------|
| 1. Guard | 4.69C.0018 |
| 2. Handle bar | 4.69C.0016 |
| 3. Handle bar | 4.69C.0017 |
| 4. Handle bar | 4.69C.0019 |
| 5. Safety bar | 4.69C.0020 |
| A. Customized | |
| Z. No accessories | |

KMP02.RF.

Switching Action / Receiver Options

1. S.P.S.T. - N/O, 0,1 A / 24 VDC, Receiver PCB with semiconductor relays up to 0,2 A; for system integration.
 2. S.P.S.T. - N/O, 0,1 A / 24 VDC, Receiver with housing; semiconductor relays up to 0,2 A, cordset.
 3. S.P.S.T. - N/O, 0,1 A / 24 VDC; Receiver with USB interface
- A. Customized

Protection

1. IP X2
- A. Customized

Receiver Cordset

1. 2 m
 2. 5 m
 3. 10 m
- A. Customized
 - Z. No Cordset

Cover Option Left & Right

- | | |
|------------------------|----------|
| 1. Cover black | RAL 9017 |
| 2. Cover graphite grey | RAL 7024 |
| 3. Cover lightgrey | RAL 7035 |
| 4. Cover blue | RAL 5017 |
| 5. Cover green | RAL 6024 |
| 6. Cover yellow | RAL 1023 |
| 7. Cover red | RAL 3020 |
| A. Customized | |

- Secure wireless contact up to 10m line of sight
- application-specific range depends on the installation location



AMP 03-RF



- Multi footswitch aluminium panel,
- Easy to operate
- Wide gap between pedals

Panel-colour

1. Black RAL 9017
 2. Graphitegrey RAL 7024
 3. Lightgrey RAL 7035
- A. Customized

Baseplate

1. ABS (Standard)
 2. Stainless Steel
- A. Customized

Accessories

Part-No.

- A. Customized
Z. No accessories

Norms

- A. Customized
Z. No Norm

AMP03.RF.

Switching Action / Receiver Options

1. S.P.S.T. - N/O, 0,1 A / 24 VDC, Receiver PCB with semiconductor relays up to 0,2 A; for system integration.
 2. S.P.S.T. - N/O, 0,1 A / 24 VDC, Receiver with housing; semiconductor relays up to 0,2 A, cordset.
 3. S.P.S.T. - N/O, 0,1 A / 24 VDC; Receiver with USB interface
- A. Customized

Protection

1. IP X2
 2. IP X7
- A. Customized

Receiver Cordset

1. 2 m
 2. 5 m
 3. 10 m
- A. Customized
Z. No Cordset

Cover option left to right

- | | |
|------------------------|----------|
| 1. Cover black | RAL 9017 |
| 2. Cover graphite grey | RAL 7024 |
| 3. Cover lightgrey | RAL 7035 |
| 4. Cover blue | RAL 5017 |
| 5. Cover green | RAL 6024 |
| 6. Cover yellow | RAL 1023 |
| 7. Cover red | RAL 3020 |
| A. Customized | |

- Secure wireless contact up to 10m line of sight
- application-specific range depends on the installation location



KHS 01- RF

- Handcontrol with 2,4 GHz Bluetooth 4.0
- Assembled to customers specification



Norms

- A. Customized
- Z. No Norm

Body colour

- 1. Black
- 2. Grey
- A. Customized

Accessories

- | Accessories | Part-No |
|-------------------|------------|
| 1. Holder | 4.69C.0012 |
| 2. Belt clip | 4.69C.0013 |
| 3. Holding clamp | 4.69C.0014 |
| A. Customized | |
| Z. No Accessories | |

KHS01.RF. 1 Z

Switching Action / Receiver Options

- 1. 1 x S.P.S.T. - N/O, 0,1 A / 24 VDC,
- 2. 2 x S.P.S.T. - N/O, 0,1 A / 24 VDC,
- 3. 3 x S.P.S.T. - N/O, 0,1 A / 24 VDC;
- 4. 4 x S.P.S.T. - N/O, 0,1 A / 24 VDC,

A. Customized

Protection

- 1. IP X2
- A. Customized

Receiver Cordset

- 1. Receiver PCB with semiconductor relays up to 0,2 A; for system integration.
- 2. Receiver with housing; semiconductor relays up to 0,2 A, 2m cordset.
- 3. Receiver with USB interface
- A. Customized

- Secure wireless contact up to 10m line of sight
- application-specific range depends on the installation location